

VAR-120-4ch Controller

"Simple and highly versatile without compromising sound masking performance and quality."



Each VAR-120-4ch rack mount controller unit provides:

- Up to 4 output channels
- Up to 30 speakers per channel
- Independent equalizer for each channel
 - 340 narrow bands automatic equalizer
 - 19 1/3 octave bands automatic or manual equalizer
- High-powered amplifier providing 88 dBA at 1m
- 4 inputs for active volume control sensors
- 4 music and paging inputs with independent 1/3 octave equalizers for each output channel
- 2 inputs for wall mounted volume control knobs

The VoiceArrest networked sound masking system highlights:

- Simple and highly versatile without compromising sound masking performance and quality.
- Multiple controller units can be networked together to construct large sound masking projects.
- Adaptive volume adjustment for optimal efficiency and comfort (US Patent 8116461 B2)
- Automatic equalization that guarantees the optimum sound masking spectra (US Patent 7460675 B2)

SPECIFICATIONS:

Outputs	
Nb Outputs	4
Max Nb Speakers/Outputs	30
Max Nb Speakers/Controller	120
Sound Masking	
Sound Masking Volume	30 to 88 dBA in 0.1 dB steps and mute
Sound Masking Equalizer	Auto-calibration process in 340 narrow bands of 19 1/3 octave bands from 100Hz to 6.3kHz
Sound Masking Ref Spectrum	13 pre-set sound masking reference spectrums, unlimited user defined spectrums
Sound Masking Volume Ramp-Up	User defined, up to 30 days
Active Volume Control	
Nb Sensor Inputs	4
Max Nb Sensors/Input	6
Control	Independent sound masking volume adjustment for each output channel
Masking Volume Change Rate	Adjustable down to 0.1 dB steps, updates every 15s
Active Adjustment Range	User defined; maximum range: -7 to +3 dB relative to reference masking level

SPECIFICATIONS:

Music and Paging	
Music and Paging Inputs	4
Music and Paging Mixer	Independent for each output channel
Music and Paging Volume	30 to 88 dBA in 0.1 dB steps and mute
Music and Paging Equalizer	18 1/3 octave bands (125Hz to 6.3kHz)
Volume Control Knobs	
Volume Ctrl Knob Inputs	2
Volume Ctrl Knob Mixer	Independent for each output channel (Sound Masking and/or Paging and Music)
Volume Range	User defined
Schedule	
Schedule	24 hour periods per day, 7 days
Volume	0.1dB steps
Transition Ramp	Instant, 2m30, 5min, 10min, or 15min
Schedule Mixer	Independent for each output channel (Sound Masking and/or Paging and Music)
Daylight Saving Time	Automatic Adjustment depending on local time zone settings
Monitoring	
24/7 system diagnosis (requires computer running Project Manager Software)	
Connectivity	
Connectivity	Wifi, Ethernet, or USB (not required for normal operation)
Wifi	WPA/WPA2 Personal or WEP, can be turned ON or OFF
Power	
Input	18-24VDC, Max 30W
Available Power Supply	50W, 120W and 160W (Higher power needed when powering multiple controllers)
Physical	
Size	430mm x 300mm x 75mm (16.9" x 12" x 3")(2U rack mount brackets available)
Weight	8.6kg (19lb)
Warranty	
Warranty	10 years
Certifications - ETL Listed 3191772	
UL 60065 / ULC 60065 - Standard for Audio, Video and Similar Electronic Apparatus - Safety Requirements	
UL 2043 - Standard for Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handling Spaces	
FCC - EN 55103 - Electromagnetic compatibility - Product family standard for audio, video, audio-visual and entertainment lighting control apparatus for professional use - Part 1: Emissions, Part 2: Immunity	
Related ASTM Standards	
ASTM E1374-06 (11) - Standard Guide for Open Office Acoustics and Applicable ASTM Standards	
ASTM E1573-09 - Standard Test Method for Evaluating Masking Sound in Open Office Using A-Weighted and One-Third Octave Band Sound Pressure Levels	
ASTM E1130-08 - Standard Test Method for Objective Measurement of Speech Privacy in Open Offices Using Articulation Index	
ASTM E2638 - Standard Test Method for Objective Measurement of Speech Privacy Provided by Closed Rooms	

Multiple controller units can be networked together to construct large sound masking projects.



1900 Firman Dr., #800
Richardson, TX 75081 USA

Phone 866-557-8438
Fax 972-526-5333

www.SpeechPrivacySystems.com
Sales@SpeechPrivacySystems.com